



Svensk Binär Teknik

NPOWER12-8221

Tænd og sluk udstyr via netværk, 12 x IEC C13 udgange, op til 10A, RJ45, RS232, 2 indgange for temp/fugt sensorer

FEATURES

- 12 port PDU with individual on / off and assembled power meter via network
- 19 "rack mount, 1U
- 2 x power supply with 230V, 16A
- User interface via web browser with Password
- Scheduled on / drain per port
- Programmable sequential power up
- 12 x IEC C13 outputs, max. 10A
- 2 x inputs for temperature and temperature / humidity sensor with alarm
- 12 x Watchdog with ping for each connected PC
- SNMP Get / Traps and Email Support
- Supports Iphone and Android



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

NPOWER12-8221

SPECIFICATIONS

Operating Temp.	:	0-50 °C
Netværk	:	10/100 Mbit/s
Dimensioner	:	43.9 x 4.4 x 19.5 cm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.