

ETH-TEMP-2111

ETH remote control over network. 4 x on / off outputs, 12 x passive input, 4 x RJ45

FEATURES

The ideal choice for Server Room and Server rack monitoring.
4 x potential-free switching relay outputs - 36VDC / 3A switches
Large LED display for power measurement, IP address, sensor data and error reports
4 x Watchdog for monitoring connected PCs (ICMP / TCP)
12 x passive signal inputs - (contact inputs) for Phoenix plugs
4 x RJ45 for temperature / humidity sensors. RS232 / 485, 1 x RJ45 for LAN
Features, limit values, alarm receivers set up on the device via supplied software
2 x 12VDC power supply inputs (redundant)
PoE - Power over Ethernet for 2111-2 the model.
Free APP for Android and iPhone
SNMP Get / Traps (SNMPv1, v2c, v3)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



Svensk Binär Teknik

ETH-TEMP-2111

SPECIFICATIONS

Operating Temp.	:	0-50 °C
Netværk	:	10/100 Mbit/s
Dimensioner	:	139 x 91 x 35 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.