

8 x Power Relay COM NO, 24VDC / 250VAC 5A, 2 x RJ45 Ethernet Modbus/TCP/UDP, 12 - 48VDC FEATURES

- Built-in Web server
- Web HMI
- Modbus TCP and Modbus UDP protocols
- 2 x RJ45 Ethernet - Daisy chain
- Good communication security
- Dual Watchdog
- Operating temperature range: $-25 \sim +75^{\circ}\text{C}$
- I/O Pair-link - input is mirrored to the other's output
- 8 x Relay power - electromechanical, COM NO
- Relæskiftetid: on: 10ms, off: 5ms
- Relay contact voltage and current: 24VDC / 250VAC / 5A
- Electromechanical: Avoid inductive load
- Supply voltage: 12 - 48VDC





Svensk Binär Teknik

ETHIO8R-I

SPECIFICATIONS

Operating Temp.	:	-25°C - 75°C
Luftfugtighed	:	10 ~ 90% RH, non-condensing
Strømforbrug	:	12 ~ 48 VDC



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.