



1 UNIT server to 19 "Rack mounting with 2 x PCIEX (X8) Expansion, SIM, 4xRS232 / 422/485, 4xusb FEATURES

- 6th / 7th Gen Intel® skylake-s / kaby lake-s i7 / i3 CPU
- Intel® Q170 Express chipset
- 2 x DDR4 Sodimol socket, max. 64GB
- Multiple Independent Display: DP, HDMI DVI
- 2 x Intel GBE LAN
- 4 x USB 3.0
- 4 x COM
- 2 x PCIE X 8 (Option: 1xPCI, 1xPClex)
- 2 x Mini PCIE
- 1 x M.2
- 2 x SIM
- 1u Rackmount Server Design





SPECIFICATIONS

CPU	:	6th / 7th Gen Intel® Skylake-S / Kaby Lake-S i7 / i5 / i3 CPU
Chipset	:	Intel® Q170
USB	:	4 x USB 3.0
Operating Temp.	:	(100 % CPU usage) -20°C to +60°C with mSATA / SSD 0°C to +50°C with HDD
Andet	:	OPTIONS GPS, Bluetooth, PoE, WiFi, 4G LTE, Isolated COM, battery UPS, DI/DO, Video Input *SATA Kit * Power adapter / Power Supply
Ethernet	:	2 x RJ45 Intel GbE
Forsyning	:	12Vdc external adapter 100/240Vac to DC 120W, Internal 150Watt
Hukommelse	:	2 x DDR4 SODIMM, Max. 64GB
Luftfugtighed	:	95% @ 40°C, non-condensing
Msata	:	storage
OS SUPPORT	:	7th Gen. Win10 IOT (64bit), Ubuntu 16.04.3 above, Fedora 26 above, CentOS 7.4 above 6th Gen. Win 10 IOT (64bit), Win 8.1 (64bit), Win Emb. 8 (64bit), Win. 7 (64bit), mbedded Sta 7 (64bit), Ubuntu 16.04.3 above, Fedora 26 above, CentOS 7.4 above
Porte	:	4 x RS232 / 422 / 485





SPECIFICATIONS

Udgange	:	1 x DP, 1 x HDMI, 1 x DVI
Udvidelser	:	2 x PCIe x 8 (Optional) 1 x Full-size Mini PCIe (PCIe / mSATA / USB) 1 x Full-size Mini PCIe (PCIe / USB)
Dimensioner	:	(WxDxH) 440W x 360D x 44.3H mm(WxDxH) 440W x 360D x 44.3H mm

