

## USB I/O Module with 10 x digitale input and 8 relay output

### FEATURES

- I/O modul
- 10 x digitale input
- 8 x relæ output (Type C)
- Forsynes via USB
- Alle DI kan bruges som 32-bit tæller
- 8kV ESD beskyttelse
- Udvidet temperatur -25 til +75 °
- Isolation: 3000 VDC
- Watchdog
- Benytter ikke driver





## SPECIFICATIONS

|                 |   |                                                                                                                               |
|-----------------|---|-------------------------------------------------------------------------------------------------------------------------------|
| Operating Temp. | : | -25 ~ +75 °C                                                                                                                  |
| Indgang         | : | Channels 10 Digital Input / Counter                                                                                           |
| Interface       | : | USB 2.0 Full-Speed                                                                                                            |
| Isolation       | : | Intra-Module Isolation, Field-to-Logic 3000 VDC                                                                               |
| LED             | : | System LED Indicators 3 LEDs as Power, Run and Error I/O LED indicators<br>Yes, 12 LEDs Digital Input/ Relay Output Indicator |
| Output          | : | 8 x Relay Output Channels                                                                                                     |
| Watchdog        | : | 1 Hardware watchdog (1.6 second) 1 Software watchdog (Programmable)                                                           |
| Dimensioner     | : | (W x L x H) 31 mm x 129 mm x 147mm                                                                                            |

