

IPP15SUN1600

15" Panel PC 1.6GHz (N3160) til sollys 1600 Nits FEATURES

Intel® Braswell Celeron 1.6GHz N3160
Res.1024 x 768 pixel
1600 nits
Touch P-CAP 10 point touch screen
Dual display: HDMI/DP
1 HDMI, 1 DP
3 USB
1 COM
2 LAN
DC 9 ~ 36V input
164mm(W) x 106.5mm(D) x 30mm(H)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



IPP15SUN1600

SPECIFICATIONS

CPU	:	Celeron® N3160 1.6GHz quad-core SoC (6W)
USB	:	2 x USB 3.0, 1 x USB 2.0
Andet	:	2 x SMA hole, Indicators 1 x Power LED Controls 1 x Power on Switch
BIOS	:	AMI
Ethernet	:	2 x Gigabit (Intel® I210)
Forsyning	:	Wide range DC 9 ~ 36V input, AC 100 ~ 240V 65W adapter, DC Jack
Grafik	:	Graphic Intel® HD graphics 400/405 by processor
Hukommelse	:	1 x DDR3L 1600MHz SODIMM,max. up to 8GB
IP-Tæthed	:	Front IP65
Materiale	:	Aluminium
Miljø	:	Opearting Temperature -20°C ~ 50°C (Optional -40°C) Storage Temperature -20°C ~ 80°C Relative Humidity 0% ~ 90%(non-condensing)
Montering	:	Panel, Option(Wall / DIN)





IPP15SUN1600

SPECIFICATIONS

Porte	:	1 x COM (RS-232/422/485, RS485 with auto flow control)
Skærm	:	4:3 Color 16.7M Pixel Pitch (H/V) 0.297mm x 0.297mm Constrast Ratio (typ.) 1000 : 1 (typ.) Viewing Angle (H/V) 160/160 (typ.) Backlight MTBF (typ.) 70,000hrs (typ.)
Touch	:	P-CAP 10 point touch screen
Udgange	:	1 x HDMI, 1 x DP
Udvidelser	:	1 x Mini-PCle (Half size), 1 x Mini-PCle (Full size, share with mSATA)
Watchdog	:	Yes
Dimensioner	:	164mm(W) x 106.5mm(D) x 30mm(H)

