

19" Panel LCD monitor, IP65 front, resistive touch
USB, 1280 x 1024, VGA, HDMI, DP, DC 24V, 250 nits,
5:4 format

FEATURES

- 19" LCD monitor
- Resolution: 1280 x 1024
- 5:4 format
- IP65 front
- 250 nits
- USB resistive Touch
- 1 x DP
- 1 x VGA
- 1 x HDMI
- 1 x USB to Touch
- 1 x Audio Input
- for Panel mounting OPTION: wall/rack or desktop mounting
- Dimensions: 482 x 55 x 380mm (with frame)
- Cutout dimensions: 407.1 x 334.6mm
- 24V DC screw type
- Weight: 6kg





SPECIFICATIONS

Operating Temp.	:	0°C ~ +45°C (+32°F ~ +113°F)
Forsyning	:	Screw-type external AC/DC EU power adapter
IP-Tæthed	:	IP65 front
Lysstyrke	:	250 nits
Mål og vægt	:	19" SXGA TFT LED
OSD	:	OSD (on screen display)
Stik	:	1 x USB 1 x DP 1 x VGA 1 x HDMI 1 x Screw-type DC power input
Tilbehør	:	1 x VGA cable 1 x USB cable for touchscreen 1 x Audio cable 1 x EU power cord
Touch	:	USB resistive touch (option RS232 on inquiry)
Weight	:	6 kg
Dimensioner	:	482 mm (W) x 55 mm (D) x 380 mm (H), Pakke dimensioner: 595 x 230 x 555 mm

