



Svensk Binär Teknik

MON10.4-1600NITS

10.4" LCD High Bright LCD Panel, 1600nits, Sunlight readable, 800 x 600, DVI / VGA, 4:3 format FEATURES

- 10.4" sunlight readable LCD open frame panel
- 4:3 format
- high brightness 1.600cd/m2
- Res. 800 x 600
- LED backlight
- DVI-D, VGA
- temperature -20°C~70°C
- Low power consumption
- MTBF: 70,000 hours
- 236(W) x 176.9(H) x 6.3(D)mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



MON10.4-1600NITS

SPECIFICATIONS

Farve	:	252K
Andet	:	Sync: LVDS, Response time typ. 25ms,
Betragtningsvinkel	:	+45~-65(H), +65~-65(V)
Grafik	:	VGA DVI
Kontrast	:	600:1
LCD	:	10.4" TFT LED Backlight 1600 Nits, SVGA
Skærm	:	Res. 800x600, Display Area 210.2 (H) x 158.4(V) mm
Weight	:	0.45Kg
Dimensioner	:	236(W) x 176.9(H) x 6.3(D)mm

