



Svensk Binär Teknik

ETH-POE-DIP-4X1G

4 Ports PoE Switch / PoE Injector 60 Watt per port.
PoE 48 or 56VDC. Gigabit. 1 X RJ45 Uplink, 4 x RJ45
PoE port.

FEATURES

- 4 x RJ45 port with PoE ++ (Ultra PoE)
- 1 x RJ 45 Uplink port (not PoE).
- 60W for every PoE-Port
- Power Budget is 120 watts
- IEEE 802.3at / by PoE.
- Dip on / off PoE
- Power supply: 100 - 240VAC
- Operating temperature: 0 - +40°C
- Size: 119 x 88 x 27 mm
- Weight: 1.3 kg



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

Operating Temp.	:	0° ~ 40°C
Buffer	:	12Kbyte
Pin	:	1/2(+), 3/6(-), 4/5(+), 7/8(-)
PoE	:	Per Port 48V or 56V DC, Max. 60 watts
Porte	:	5 x GE ports Auto-MDIX, 4 x ports PoE / PoE+ (Ultra PoE)
Standarder	:	IEEE 802.3 10-BASE-T (Ethernet) IEEE 802.3u 100-BASE-TX (Fast Ethernet) IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) IEEE 802.3x Flow Control (full-duplex flow control) IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet Plus
Dimensioner	:	119 x 88 x 27 mm

