

Industrial 2 x RS-422/485 PCI-Express Serial Card with Surge and Isolation Protection with High and Low Back Plate

FEATURES

- 2-port RS-422/485
- Communication speeds up to 921.6 Kbps.
- 2KV overvoltage protection, IEC-61000-4-5 Level 3.
- 1.5KV insulated protection meets IEC-60747 -5-5
- 16C950 UART controller
- RS-422 and RS-485 auto detection and switching technology
- jumper and software free.
- On-chip hardware automatic flow control to guarantee nothing data loss.
- 15KV ESD protection for all serial signals meets IEC-61000-4-2 standard.
- Plug-n-Play, I / O address and IRQ assigned by BIOS.
- Certified by CE , FCC, VCCI, BSMI, RoHS and Microsoft WHQL authentication.
- Windows 11 24H2 64 bit
- Windows 11 23H2 64 bit
- Windows 11 22H2 64 bit
- Windows 11 21H2 64 bit
- Windows 10 22H2 (22H2) 32/64 bit
- Windows 10 21H2 (21H2) 32/64 bit
- Windows 10 21H1 (21H1) 32/64 bit
- Windows 10 20H2 (20H2) 32/64 bit
- Windows 10 20H1 (2004) 32/64 bit
- Windows 11 IoT Enterprise 24H2
- Windows 11 IoT Enterprise LTSC 2024
- Windows 11 Enterprise LTSC 2024
- Windows 10 IoT Enterprise 22H2
- Windows 10 IoT Enterprise 21H2
- Windows 10 IoT Enterprise LTSC 2021
- Windows 10 Enterprise LTSC 2021 32/64bit
- Windows Server 2022 64bit





SPECIFICATIONS

Andet	:	Option: PCIe card holder ask for price!
Beskyttelse	:	±15KV ESD IEC-61000-4-2 Air Discharge ±8KV ESD IEC61000-4-2 Contact Discharge ±4KV ESD IEC61000-4-2 Level 2 Line-to-Line 2KV Surge IEC61000-4-5 Level 3 Surge Immunity Test 1.5 KV Isolation IEC60747-5-5 Hi-Pot
FIFO	:	128byte Hardware
Hastighed	:	50bps ~921.6Kbps, Stop bit 1, 1.5,2, Parity even,odd,none,mark,space
Kabel	:	DB44 til 4 x DB9 male , 40CM
PCI	:	PCI express 2.0 x 1 (single lan)
Porte	:	4 x RS422/485
Signaler	:	RS-422: TxD+, TxD-, RxD+, RxD-, GND 4-wire RS-485: TxD+, TxD-, RxD+, RxD-, GND 2-wire RS-485: Data+, Data-, GND
Stik	:	DB44 Female

