

10.4 "Rugged PC tablet, IP65, LED 1024 x 768, Wifi, resistive touch, 1000 nits

FEATURES

- 12" Robust Tablet PC with IP 66
- Intel® Core™ i5-6300U 2.4GHz
- 4GB DDR3L RAM, upgradeable to 32GB
- M.2 2280 SSD, SD SLOT
- Windows 10 IoT Enterprise
- built-in 3-axis sensor, dual speaker
- 1200 nits LED backlight
- Resistive touch, support defroster function
- 9 x programmable button
- 2 x contrast adjustment button
- 2 x sound adjustment button
- 2 x RS232 (COM1 with power), RS-232/422/485
- 2 x USB 2.0 / 3.0, USB 2.0
- 1 x CAN bus (SAE J1939 / OBDI II supported)
- 1 x Audio jack
- Vesa 75/100 mounting
- Power supply 9-60V DC





SPECIFICATIONS

CPU	:	Intel® Core™ i5-6300U 2.4GHz
Operating Temp.	:	Operating temperature -30°C to +55°C
Chok/Vibration	:	MIL-STD-810G, Method 514.7 c2/c3/c4
Harddisk	:	M.2 2280 SSD, SD slot
Hukommelse	:	4GB DDR3L SODIMM, expandable to 32GB
I/O	:	1 x RS232, 1 x RS-232/422/485, 1 x USB 3.0, 1 x USB 2.0, 1 x CAN bus, 2 x DI, 2 x DO, 1 x Audio jack
Kontrast	:	1200 Nits
Netværk	:	Dual Gigabit Ethernet (RJ45)
Skærm	:	12.1" XGA TFT LCD with LED backlight (1024 x 768)
Software	:	DashON
Strømforsyning	:	9~60 VDC input
Touch	:	5-wire resistive touch supports defroster function





Svensk Binär Teknik

TABLET12-RV

SPECIFICATIONS

Weight	:	Weight : 4.83 kg, 4.90 kg with IPBOX
Dimensioner	:	325 x 280 x 67 (mm)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.