

19 "TFT monitor with 350-nits LCD, with electricity without touch, dust and leakproof IP66, Dual AC / DC inputs,

FEATURES

19 "TFT metal monitor LED backlight, IP66
 1280 x 1024
 350 nits, 1000: 1, 5: 4
 Response time: 5ms
 viewing angle: 170 ° / 160 °
 3 x BNC
 2 x DVI-I (29-pin DVI-D female)
 1 x VGA (15-pin D-sub female)
 1 x RS232 / 422/485 (software selectable terminal blocks)
 100 to 240 VAC, 24 VDC (18 to 30 V)
 -15 to 55 ° C (5 to 131 ° F)
 weight: 9,700 g
 483 x 444 x 82 mm
 Panel mounting
 RoHS, CRoHS, WEEE
 Optional: RS-232: Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND
 Optional: RS-422: Tx +, Tx-, Rx +, Rx-, GND
 Optional: RS-485-2w: Data +, Data, GND
 Optional: RS-485-4w: Tx +, Tx-, Rx +, Rx-, GND





SPECIFICATIONS

Antal farver	:	16.7M (8-bit/color)
Betragningsvinkel	:	170°/160°
Forsyning	:	100 to 240 VAC, 24 VDC (18 to 30 V)
I/O	:	3 x BNC, 2 x DVI-I, 1 x VGA
Kontrast	:	1000:1, 350 nits, 5:4
Pixels	:	1280 x 1024
Porte	:	1 x RS232/422/485 (software valgt terminal blok)
Weight	:	9,700 g
Dimensioner	:	483 x 444 x 82 mm

