

15 "monitor with 1000-nits LCD with electric without touch, dust and leakproof IP66, Dual AC / DC inputs, FEATURES

24 "TFT metal monitor with capacitive touch, IP66, IP20
 LED backlight
 1280 x 1024
 1000 nits, 700: 1, 4: 3
 Display angle: 160 ° / 140 °
 1 x DVI-I (29-pin DVI-D connectors female)
 1 x VGA (15-pin D-sub connector female)
 1 x RS-232 (DB9 male)
 1 x Optional RS232 / 422/485
 Supply: 100 to 240 VAC, 24 VDC (18 to 30 V)
 Desktop, Panel mounting
 Weight: 6,100 g
 429 x 387 x 75 mm
 -40 to 70 ° C
 CISPR 32, FCC Part 15B Class A
 EN 55032/24
 Optional: RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND < Optional: RS-422: Tx +, Tx-, Rx +, Rx-, GND
 Optional: RS-485-2w: Data +, Data, GND
 Optional: RS-485-4w: Tx +, Tx -, Rx +, Rx, GND





SPECIFICATIONS

Operating Temp.	:	-40 to 70°C
Antal farver	:	16.7M (8-bit/color)
I/O	:	1 x DVI-D, 1 x VGA
IP-Tæthed	:	IP66, front IP20, rear
Kontrast	:	1000 cd/m2, 700:1, 4:3
Luftfugtighed	:	5 to 95% (non-condensing)
Porte	:	RS-232 ports x 1 (DB9 male) RS-232/422/485 ports x 1, software-selectable (terminal block)
Weight	:	6,100 g
Dimensioner	:	429 x 387 x 75 mm

