

Fanless embedded PC with Intel® Braswell SoC Processor, 1.6GHz, with HDMI

FEATURES

- Intel® Celeron® N3060, 1.6GHz
- 2 x 204 pin DDR3L SO-DIMM Socket.
- 1600MHz SDRAM up to 8GB (2GB DDR3L SO-DIMM pre-installed)
- Chipset: SoC Integrated, Intel® HD Graphics 400
- Hard drive: mSATA, MicroSD socket
- 1 x Serial ATA port with 600MB / s HDD transfer rate
- 2 x Realtek 8111HS GbE controllers (LAN chipset)
- 1 x Micro -B RS232 half-duplex
- 4 x USB 3.0 ports, 1 x Micro-B USB 2.0, 2 x RJ-45 ports for GbE
- 2 x HDMI, Max. resolution: 3840 x 2160
- 1 x 3.5mm stereo headphone jack
- Supports 2/4 / 5.1 / 7.1 channel configurations via HDMI
- Operating temperature: -10 ~ 55 ° C, Moisture: 0% -85% RH @ 55 ° C
- 0.86 KG, 141 x 34.8 x 107.6
- OS Support: Windows® 7 / Windows® 10 / Linux (Kernel: 3.1X)



SPECIFICATIONS

CPU	:	Soldered onboard Intel® Celeron® N3060, 1.6GHz
Chipset	:	SoC Integrated
Operating Temp.	:	-10 ~ 55 °C
Chok/Vibration	:	3 Grms/5~500Hz/random operation, Operating 50G (11ms), Non-operating 80G with eMMC
Grafik	:	Intel® HD Graphics 400
Harddisk	:	1 x mSATA, 1 x MicroSD socket,
Hukommelse	:	2 x 204-pin DDR3L SO-DIMM socket, supporting 1600MHz SDRAM up to 8GB (2GB DDR3L SO-DIMM pre-installed)
I/O	:	1 x Micro-B RS232 half-duplex, 4 x USB 3.0 ports, 1 x Micro-B USB 2.0, 2 x RJ-45 ports for GbE, 2 x HDMI, 1 x 3.5mm stereo headphone jack, 1 x Half-size Mini-PCle slot
Luftfugtighed	:	0%-85% RH @ 55 °C (non-condensing)
Montering	:	Support VESA-mount
OS SUPPORT	:	Windows® 7 / Windows® 10 / Linux (Kernel: 3.1X)
Strømforbrug	:	Max. 15W (w/o I/O card)





Svensk Binär Teknik

EPC-BW-2ETH2HDMI

SPECIFICATIONS

Watchdog	:	1~255 levels reset
Weight	:	0.86Kg
Dimensioner	:	141 x 34.8 x 107.6mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.