

ESW8G-M-SFP4P

Managed Switch, 8 Ports 100/1000Mbit RJ45, PoE+ (36W), 2 x 100Mbit / 1Gbit SFP, 2 x 10Gbit SFP FEATURES

- 8 x 10/100 / 1000BASE-T RJ45 Auto-MDI / MDIX Ports
- 2 x 1000BASE-SX / LX / BX SFP Interface
- 8 POE Injector Ports with 802.3at / of PoE Standard 802.3at
- 60GB non-blocking
- 32Mbits Data buffer
- IEEE 802.3X pause frame for duplex
- IP30 aluminum
- Din rail kit and wall mounting
- Alarm relay 1A, 24V DC
- 2 x Digital output (DI)
- 2 x Digital output (DO) 24v DC, 100mA max
- Dimensions: 72 x 107 x 152mm
- Weight: 1684g & nbsp;
- Supply: 48-56 V DC



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

Båndbredde	:	500kb - 1000Mbps
Forsyning	:	Dual 48-56V DC, max 11.1 watts, max 306 watts (med PoE)
Indgang	:	Pin 1/2 for power, pin 3/4 for alarm, Pin 5/6 for power 2,
Indgang	:	2 x Digitale indgange
IP-Tæthed	:	IP30
Montering	:	DIN rail installation med væg montering
PoE	:	8 x 802.3at/af PoE injector fucnktion
Porte	:	8 x 10/100/1000BASE-T, 2 x 1000BASE-SX/LX-BX SFP, 2 x 10GbBASE-SR/LR SFP+
Standarder	:	IEEE 802.3at/af Power over Ethernet PLUS/PSE
Udgange	:	2 x digitale udgange
VLAN	:	protokol baseret, Voice, MVR (Multicast VLAN registration), op til 255 VLAN grupper
Weight	:	1684g





Svensk Binär Teknik

ESW8G-M-SFP4P

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.