

900 Mbit 5GHz Outdoor Access Point with built-in dual-polarized antennas. PoE+, IP55, -20 - +70°C FEATURES

- 5GHz, 900Mbps AP, Gateway, Repeater, Bridge, WISP
- 802.11 b/g/n/ac
- 2T2R architecture with dual-polarizing 14dBi antennas built-in
- Transmission power: 100mW
- 2 x 10/100/1000Mbps RJ45 Ethernet
- For pipe mounting and wall mounting - clamping band included
- Supports WAN connection in DHCP, Static IP, PPPoE
- WPA/WPA2, WPA-PSK/WPA2-PSK and 802.1X RADIUS authentication
- IP55
- Power supply: PoE+ (48Vdc) or 12VDC 1A (via DC jack)
- Operating temperature: -20 - +70°C
- Dimensions: 260 x 87 x 38 mm





SPECIFICATIONS

Operating Temp.	:	-20 ~ 70 degrees C
Antenne	:	Built-in 14dBi directional antenna with dual polarization
Input	:	48V DC IN,0.5A, IEEE 802.3 at PoE+ or 12V DC IN, 1.0A from DC Jack
IP-Tæthed	:	IP55
Kanaler	:	FCC: 36, 40, 44, 48, 149, 153, 157, 161, 165 (9 channels), ETSI: 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 132, 136, 140 (16 channels)
Modes	:	Access Point, Gateway, Repeater, WDS (AP/Bridge/Station), WISP
Mål og vægt	:	87 x 38 x 260mm / 405g
Sikkerhed	:	WPA/WPA2, WPA-PSK/WPA2-PSK and 802.1X RADIUS authentication

