

7 ports industrial PoE + gigabit unmanaged switch, 4 x RJ45, 2 x SFP

FEATURES

- 4 x 10/100 / 1000Tx IEEE 802.3at PoE + Compliant with 30W per Port
- 1 x 10/100 / 1000Tx & nbsp;
- 2 x 100/1000 SFP
- Auto MDI / MDI-X Function < br> 14Gbps Back-Plane (Switching Fabric)
- 8K MAC Address
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- Power Supply: 12 ~ 36VDC
- Built-in 1 x Relay Output for Power Failure Detection
- IP30 Rugged Metal Case Design
- Your rail and wall mounting
- Operating temperature -40 ° to 75 ° C
- Dimensions: 46 x 99 x 142mm
- Weight : 1.4 Lb





ANR-LNP-0702G-F-24T

SPECIFICATIONS

Operating Temp.	:	40° to 75°C
Approval	:	EMI, EMS, RF, RF Radiation Exposure, EN60950-1 CNS14336-1, RoHS Compliant
I/O	:	5 x RJ45 Ports w/ 4*10/100/1000Tx (PSE 30W/Port), and 1*10/100/1000Tx, 2 x 100/1000 SFP Slot
IP-Tæthed	:	Metal, IP30 protection
Luftfugtighed	:	5 to 95%, (non-condensing)
Montering	:	Din skinne og væg montering
Netværk	:	10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5 1000Base Tx: 2-pair UTP/STP Cat. 5/5E
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx Ethernet IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+
Strømforbrug	:	145 Watts
Strømforsyning	:	12~36VDC, Redundant Input
Switch	:	14,880pps for Ethernet Port 148,800pps for Fast Ethernet Port 1,488,000pps for Gigabit Ethernet Port, 10Gbps Back-Plane (Switching Fabric)
Weight	:	Unit 1.4 lb. Shipping Weight 1.8lbs





Svensk Binär Teknik

ANR-LNP-0702G-F-24T

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.