

GSM Alarm with 2xDin, 2xain and 2XDO. Alarms for mobile phone via SMS or Call, APP, 4G

FEATURES

- 2 x digital inputs NC / NO type
- 2 x analog inputs. 12 Bit resolution, 0-5V, 4-20mA or 0 - 20mA
- 2 x Relay outputs 5A / 30VDC, 5A / 250VAC
- 1 x USB port
- GSM 3G 4G
- 9-36VDC (12V / 300mA)
- Backup Battery 3.7V 1200mAh
- Operating temperature -10- + 70 ° C
- Custom SMS Alarm Messages
- APP for iOS and Android





SPECIFICATIONS

Operating Temp.	:	-10 to +70 °C
Frekvens	:	GSM 850/900/1800/1900Mhz or 3G UMTS/HSDPA
Indgang	:	2 x Digital input, NC/NO/Edge/Level type, Can be used as Pulse Counters;
Indgang	:	2 Analog Inputs. 12 bit resolution, 0-5V or 0-20mA or 4-20mA;
Input	:	DC 12V/1.5A Range 9-36VDC
Relæ	:	2 X Rated: 5A/30VDC,5A/250VAC
Strømforbrug	:	Standby:12V/70mA; Working Max.: 12V/300mA
Weight	:	1000 g
Dimensioner	:	168 x 113 x 32.3mm

