

Embedded fanless system with Celeron® CPU N3160 (1.6 Ghz / 4core), up to 8GB, mSATA & SATA SSD or HDD

FEATURES

- Cost effective with fanless and cableless design
- Intel® Celeron® processor N3160 (1.6 GHz / 4-core)
- 2 x RS-232/422/485 ports
- 4 x USB ports
- 2 x isolated 10/100/1000 Mbps Ethernet ports
- 1 x PoE PD compatible with IEEE 802.3at standard LAN 1
- 1 x DIO port
- 2 x PCI Express Mini Card slots (3G / GPRS & Wi-Fi)
- 1 x mSATA & amp; SATA SSD (or HDD)
- 12 to 24 VDC
- Weight: 1.50 KG
- Dimensions: 48 x 110 x 155 mm
- DIN rail and wall mounting
- OS support: Windows® 7 Embedded, Windows® 8 Embedded, Windows® 8, Windows® 10, Linux support package





SPECIFICATIONS

CPU	:	intel® Celeron® processor N3160 (1.6 GHz/4-core)
USB	:	2 x USB 3.0 2 x USB 2.0
Operating Temp.	:	-20°C to +60°C
Farve	:	Sølv
BIOS	:	AMI UEFI BIOS
Beskyttelse	:	DC version OVP, reverse protection
Chok/Vibration	:	2 Gms (5 to 500Hz, amplitude 0.35 mm; operation/storage/ transport
Harddisk	:	1 x mSATA 1 x SATA SSD (or HDD)
Hukommelse	:	1 x DDR3L-1600 SO-DIMM, op til 8GB
Luftfugtighed	:	10% to 95%
Montering	:	Din skinne og væg montering
Netværk	:	2 x 10/100/1000 Mbps Ethernet (Intel® i211AT) 1 x PoE PD compliant with IEEE 802.3at standard through LAN 1





EPC-PB-1.6GHZ

SPECIFICATIONS

Porte	:	2 x RS-232/422/485 (COM 1/2) with DB9, 2 x USB 3.0, 2 x USB 2.0, 2 x 10/100/1000 Mbps Ethernet, DC terminal block: 12 to 24V DC-In, VGA (DB15 connector),
Software	:	AXView 2.0 Intelligent Remote Management Solution for IoT
Strømforsyning	:	DC terminal block: 12 to 24V DC-In PoE: IEEE 802.3at
Trådløs	:	1 x Full-size PCI Express Mini Card slot 1 x Full-size PCI Express Mini Card slot with mSATA 1 x SIM card socket 3 x Antenna
Weight	:	1.50 KG
Dimensioner	:	48 x 110 x 155 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk