

Thermal Imaging Bullet Network Camera 1280×1024 25/30fps

FEATURES

- Uncooled VOx Micro bolometer with 640×512 resolution
- 9/15/25/35/50 mm fixed lens optional
- Sensitivity $\leq 40\text{mK}$
- Support temperature monitoring and alarm
- Support humanoid/vehicle detection, fire point detection
- Intelligent function: intrusion, single line crossing, double line crossing, loitering, wrong way, enter area, leave area
- Support 3 temperature measurement rule types (spot, line, area)
- Temperature measurement range: $-20^{\circ}\text{C} \sim 150^{\circ}\text{C}$ ($-4^{\circ}\text{F} \sim 302^{\circ}\text{F}$)
- Support DC12V/PoE/AC24V power supply
- IP66





SPECIFICATIONS

Operating Temp.	: -20°C ~ 150°C (-4°F ~ 302°F)
Alarm	: Temperatur alarm, I/O alarm
Alarm	: ver temperature alarm, Temperature difference alarm
Ethernet	: RJ-45 (10/100Base-T)
Indgang	: Max 10 brugere
Interface	: Ethernet, RS485, BNC, Reset knap,
IP-Tæthed	: IP66, MEtal
Linse	: Fixed, Manuel focus, 25mm
Pixels	: 640(H) x512(V)
Protokol	: IPv4/IPv6 ,HTTP,RTSP/RTP/RTCP, TCP/UDP, DHCP, DNS, PPPOE, SMTP, SIP ,802.1x
Strømforsyning	: DC12V/POE/AC24V
Type	: Uncooled IRFPA Microbolometer





Svensk Binär Teknik

KAM-TERMO-BULL

SPECIFICATIONS

Zoom	:	16X digital zoom
Weight	:	1900g
Dimensioner	:	ø110×388mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.