

10-Port Industrial Unmanaged Switch, 2 FTP Ports FEATURES

- Supporter 8-Port 10 / 100Tx
- 2 Gigabit Combo Ports
- 6 x RJ45 Port 10 / 100Tx
- 2 x 10/100/100 RJ45
- 2 x 100/1000 SFP Slots
- Supporter Auto MDI / MDI-X
- Non-Blocking Switching Fabric
- 8K MAC Address
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- UL Class I, Division 2 Certified
- Redundant Power Input Design: 12 ~ 48VDC
- 1 x built-in relay Output for Power Failure warning
- IP30 Rugged Metal Case Design
- DIN rail and wall mounting
- Operating temperature STD: -10 ° to 70 ° C





SPECIFICATIONS

Operating Temp.	:	STD: -10° to 70°C
Approval	:	EMI, EMS, FCC Class A,
Buffer	:	4Mbps (buffer)
Forbindelse	:	1 removable 6-contact terminal block
Luftfugtighed	:	5 to 95%, (non condensing)
Netværk	:	10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5 1000Base Tx: 2-pair UTP/STP Cat. 5/5E
Porte	:	6*RJ45 Ports w/10/100Tx , 2 *RJ45 Ports w/10/100/1000TX Ethernet and 2*100/1000 SFP Slot
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber
Strømforbrug	:	10W
Strømforsyning	:	12~48VDC, Redundant Input
Dimensioner	:	46 x 99 x 142 mm (W*D*H)

