



Svensk Binär Teknik

ANR-LNP-800AGH

8-Port Industrial Gigabit Switch with PoE +, unmanaged, 12-36VDC

FEATURES

- 8 x 10/100 / 1000Base-T (X) RJ45
- PoE (P.S.E.) Ports
- IEEE 802.3at
- Up to 30 Watts Per Port
- 9.6Kbytes Jumbo Frame
- Supply Voltage, Dual Wide Range 12 ~ 36VDC
- Auto-Negotiation & Auto-MDI / MDI-X
- Store-and-Forward Transmission, Flow Control,
- IP-30 Housing Design
- DIN Rail and Wall Mounting for UL Class I, Division 2 Certified



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

Operating Temp.	: STD: -10° to 60°C
Chok/Vibration	: IEC60068-2-32, IEC60068-2-27
Luftfugtighed	: 5% to 95%, (non-condensing)
Montering	: DIN-skinne og væg montering
Netværk	: 10Base Tx: UTP/STP Cat. 3,5 100Base Tx: UTP/STP Cat. 5 1000Base Tx: UTP/STP Cat.5/5e/6
PoE	: V+, V+, V-, V-, for pin 1, 2, 3, 6 (End span, MDI-X Alternative A)
Porte	: 8 x RJ45, 10/100/1000BaseTx (PSE: 30W/Port) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
Standarder	: IEEE 802.3 10Tx Ethernet IEEE 802.3U 100Tx Fast Ethernet IEEE 802.3ab 1000Tx Gigabit Ethernet IEEE 802.3x Flow Control for Full Duplex IEEE 802.3at/af PoE (Power-over-Ethernet)
Strømforbrug	: 10 Watts (no PD included)
Strømforsyning	: 12-36VDC Redundant input, PoE output 30W @ 12~36VDC (per PoE port)
Dimensioner	: 41.0 x 144.3 x 94.9 mm

