

12-port industrial Gigabit Switch with PoE + unmanaged. 8 x RJ45 ports and 4 x SFP ports, 48-55VDC

FEATURES

- 8 x 10/100 / 1000Tx RJ45 (30W / port)
- 4 x 100/1000 SFP Ports
- Auto MDI / MDI-X Function
- Store-and-Forward Switching Architecture
- 24Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- Supply Voltage: 48 ~ 55VDC
- Built-in Relay Output to Power Failure
- IP30 Rugged Metal Case Design
- DIN Rail and Wall Mounting
- Operating Temperature STD: -10 ° to 70 ° C



SPECIFICATIONS

Operating Temp.	:	-10° to 70° C
Buffer	:	7,926pps (default)
Chok/Vibration	:	IEC60068-2-32, IEC60068-2-27
Ethernet	:	8*10/100/1000Tx RJ45 (w/8*PSE: 30W/Port)
Fiber	:	4*100/1000 SFP Slot
Forbindelse	:	1 removable 6-contact terminal block
Luftfugtighed	:	5% to 95%, (non-condensing)
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+
Strømforbrug	:	15 Watts Full load w/PoE 215W@48V / 255W@51~55V
Strømforsyning	:	48-55VDC
Dimensioner	:	46 x 99 x 142 mm (W*D*H)

