



Svensk Binär Teknik

ANR-LNP-2602G-SFP

26-Port industrial 1U 19" rackmount PoE+ Gigabit unmanaged switch

FEATURES

- 24 x 10/100/1000Tx RJ45 (30W/port) IEEE 802.3at PoE+
- 2 x Gigabit combo (2 x RJ45, 2 x FTP)
- Auto MDI/MDI-X Function
- Store-and-Forward Switching Architecture
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- Power supply: 48~55VDC
- Built-in relay Output for Power Failure
- 1U 19" Rackmount design
- Operating temperature STD: -10° to 70° C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

Operating Temp.	:	STD: -10° to 70° C
Approval	:	EMI: FCC Part 15 Subpart B Class A, CE EN 55022 Class A, EMS: IEC61000-4-2 (ESD), IEC61000-4-3 (RS), IEC61000-4-4 (EFT), IEC61000-4-5 (Surge), IEC61000-4-6 (CS), IEC61000-4-8 (Magnetic Field)
Buffer	:	4Mbits
Chok/Vibration	:	IEC60068-2-32, IEC60068-2-27
Ethernet	:	24*10/100/1000Tx RJ45 (w/24*PSE: 30W/Port)
Fiber	:	Combo porte: 2*RJ45 Ports w/10/100/1000Tx Ethernet and 2*100/1000 SFP Slot
Luftfugtighed	:	5% to 95%, (non-condensing)
Montering	:	1U 19" Rackmount
Netværk	:	10BaseTx: UTP/STP Cat. 3,5 100BaseTx: UTP/STP Cat. 5 1000BaseTx: UTP/STP Cat.5/5e/6
PoE	:	30 Watts max. per PoE port
Protokol	:	CSMA/CD
Relæ	:	24 VDC, 1A resistive





Svensk Binär Teknik

ANR-LNP-2602G-SFP

SPECIFICATIONS

Strømforbrug	:	24 Watts for System
Strømforsyning	:	48~55VDC, Redundant Input
Dimensioner	:	440 x 44 x 200 mm (W x H x D)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.