

ETH-RJ45-SFP-P+T

Media converter 100/1000Mbit fiber SFP to RJ45
10/100/1000Mbit. 100/1000Mbit SFP slot, SM or MM
PoE+ PSE

FEATURES

Media converter for 100/1000Base-X SFP transceiver
The SFP module is standard for LC connectors, duplex, Single Mode / Multi Mode.
Purchase additional Gigabit SFP modules.
1 x RJ45 10/100/1000Base-TX PoE+
1 x SFP 100/1000 Mbit
Power supply: 48-56VDC
Additional purchases, if any DC48V/1.25AD
End-span PoE (1/2(+), 3/6(-))
PoE power is max. 36 Watt
DIN rail or wall mounting
Temperature: -40 to +75°C
Dimensions: 30 x 70 x 104 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

IP-Tæthed	:	IP30
LED	:	System: Power 1, Power 2 and Fault LED (Green) Fiber port: LNK / ACT (Green) 10/100/1000Base-T port: LNK / ACT, PoE In-use (Green / Orange)
Maks. afstand	:	RJ45 100m
Montering	:	DIN-rail kit and wall-mount ear
PoE	:	Understøtter PoE-effekt op til 36W for PoE-port
Stik	:	RJ45 hunstik og SFP fiberstik
Temperatur	:	-40 til +75°C
Type	:	1-Port RJ-45 interface, auto-negotiation and auto MDI / MDI-X
Understøtter	:	Understøtter IEEE 802.3at/af af PoE+ standarden, kan levere op til 36 Watt. Ud på ben 1/2 (+), 3/6(-)
Weight	:	251g
Dimensioner	:	30 x 70 x 104 mm

