

Outdoor RFID reader with PoE, IP65, IP67 with 1 x relay. 125khz em, 13.56MHz Mifare

FEATURES

- Outdoor RFID reader 125kHz EM 13.56 Hz MIFARE, MIFARE Plus, DESFire / EV1 Felica IP65, IP67
- Vandal safe IK08
- Supporter up to 200,000 users
- 1 GHz CPU to 4 GB flash + 64MB RAM
- Multi buzzer
- Driftstempereatur: -35 - 65 C
- Weight: 144g
- Dimensions: 48 x 145 x 27 mm | RS-485 Master or slave
- 10/100 Mbps ethernet
- 1 x Relay
- PoE
- Supply voltage: 12V DC





SPECIFICATIONS

CPU	:	1 GHZ
Operating Temp.	:	-35°C ~ 65°C
Forsyning	:	DC 12 V / DC 24 V
Hukommelse	:	4 GB Flash + 64 MB RAM
Indgang	:	200,000 bruger kan oprettes
IP-Tæthed	:	IP65, IP67
LED	:	Flere farver
Luftfugtighed	:	0% ~ 95%, non-condensing
Netværk	:	10/100 Mbps, auto MDI/MDI-X
PoE	:	Supported (IEEE 802.3af compliant)
Porte	:	RS485, 1ch Master or Slave (Selectable)
Relæ	:	1 x Relæ





Svensk Binär Teknik

ADGANG-RFID-POE

SPECIFICATIONS

Weight : Device: 144g, Bracket: 30g (Including washer and bolt)

Dimensioner : 48 x 145 x 27



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.