

17 "Panel PC 6.gen, projected capacitive touch,
1000Nits to sunlight, 9 ~ 36VDC supply IP66 FRONT,
the front Smooth

FEATURES

17" TFT-LCD Projected Capacitive Touch.
Intel 6th Gen. Core i3 built-in i3-6100U / i5
(option).
1 x 260Pin SO-DIMM DDR4 up to 16GB 2133MHz.
Flat front panel meets IP66
die-cast aluminum Chassis Fanless design
DC 9 ~ 36V wide range Power Input
Udskæringsmål : 422x331mm
Mål: 439x348x64.8mm (WxHxD)

OPTION: CAN Bus, UPS battery, 4 xUSB
OPTION: OPTICAL bonding for direct sunlight





SPECIFICATIONS

CPU	:	Onboard Intel 6th Core i3/ i5(option) Processors
USB	:	2 x USB 3.0 type A
Operating Temp.	:	Operating temperature(°C)0~50°C
Approval	:	CE / FCC, Class A
Ethernet	:	2 x GbE LAN RJ-45
Forsyning	:	inputDC 9~36V 1x3-pin DC Power input terminal / 1 x 2-Pin Power Switch
Hukommelse	:	1 x 260Pin SO-DIMM DDR4 up to 16GB 2133MHz
Luftfugtighed	:	humidity10 to 90%@ 40°C, non-condensing
Lyd	:	1 x Audio Line Out
Montering	:	Panel Mounting / VESA 100 x 100
OS SUPPORT	:	Windows 7 64 bit / Windows 8 64 bit / Windows 10 IoT 64 bit
Porte	:	1 x DB-9 RS-232/422/485, COM1 (Default RS-232)1 x RS-232 DB-9, COM2





Svensk Binär Teknik

IPP17-IX-1000NITS

SPECIFICATIONS

Touch	:	Projected Capacitive Touch Interface OPTION: RESISTIV TOUCH
Weight	:	6.25Kg
Dimensioner	:	(mm)439 x 348 x 64.8



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.