



Svensk Binär Teknik

CNV-SFP1G-S40

1.25Gbps SFP module Single Mode fiber LC up to 40 km

FEATURES

- Data-rate of 1.25Gbps for fiber cables
- 1310nm DFB laser and PIN photodetector for 40km transmission
- compatible with SFP MSA and SFF-8472 with duplex LC receptacle
- Compliant with SONET OC-24-LR-1 and RoHS
- Switch to switch interface
- Router/server interface
- +3.3V single power supply
- Operating temperature: 0 to +70°C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

CNV-SFP1G-S40

SPECIFICATIONS

Operating Temp.	:	0 to +70°C, Udvidet : -40 to +85°C
Afstand	:	40 KM afstand med 1310nm DFB laser og photodetector
Data	:	Data-rate of 1.25Gbps operation
Forsyning	:	+3.3V single power supply
Stik	:	LC



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.