



Svensk Binär Teknik

RFID-USB-DESFIRE

RFID Reader / Write, USB to Desfire TAG 13.56MHz, Including API Development Tool

FEATURES

- Supporter NXP Desfire EV1 / EV2 Read / Write
- Supporter Desfire Tags
- Supporter Auto Read Desfire UID / Block
- Reading distance: Up to 5 cm
- built-in two-color LED and Buzzer
- API Development Shooting Included
- Support Decimal, HexideCimal and ASCII ID Formats
- Supply Voltage: USB from PC
- Unique Serial Number Identification (UID)
- Operating temperature: -20 to + 65 ° C
- Dimensions: 62.3 x 87.7 x 18.4 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

USB	:	Kompatibel med 2.0 USB
Operating Temp.	:	-20°C to 65°C
Forsyning	:	5V DC fra USB til PC
Frekvens	:	13.56MHz
Features	:	NXP DESFire EV1/EV2 read/write. format DESFire tag, auto read DESFire UID/block, decimal, hexadecimal and ASCII ID formats
Læseafstand	:	5 cm
RFID	:	DESfira tags kompatibel
Dimensioner	:	62.3 W x 87.7 H x 18.4 D (mm)

