

4 ports PoE injector++, 95 Watt, 4 x into LAN, 4 x LAN out with PoE++, PoE 48-54VDC, Gigabit DIN, 48 - 54VDC, -40 - +75°C

FEATURES

- Connect switches without PoE for PoE PSE to Equipment
- IEEE 802.3bt back compatible to IEEE 802.3at
- Supports 10/100 / 1000Mbit speeds
- 4 x LAN input from the switch without PoE
- 4 x LAN with up to 95 Watt PoE
- Max. PoE power total is 240Watt (PoE power budget)
- Auto-detect devices with PoE input for not destroying not PoE
- Supply voltage: 48 - 54VDC max. 244 Watt
- Setting with DIP switches
- DIN bracket for wall mounting and
- Operating temperature: -40 - +75°C
- Dimensions: 135 x 88 x 50 mm
- Weight: 537g





Svensk Binär Teknik

ETH-POE4GH+

SPECIFICATIONS

Data	:	10/100/1000Mbit
Forsyning	:	48 - 54VDC 244 Watt ved maks. PoE effekt
Kabinet	:	Metal, IP30, DIN-beslag
Weight	:	537g
Dimensioner	:	135 x 88 x 50 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.