

FIBER-BYPASS-LCS

2 Channel Fiber optic bypass switch, up to 100Gbps,
LC single mode, the switching time 8mS, 9 - 48VDC,
24VAC, -40 - +75°C

FEATURES

- 2-kanals duplex eller 4-kanals simplex fiber optisk bypass omskifter
- Fiberhastigheder 100 Gbps/40 Gbps/10 Gbps/1 Gbps/100 Mbps
- Single Mode med LC-stik
- Optisk Bypass fall back omskifter
- Swiche-tid <8ms
- 1dB Insertion loss (gennemgangstab)
- Meget stor pålidelighed på kritiske netværkslink
- IP30 tæt metalhus
- Forsyningsspænding 9 ~ 48VDC eller 24VAC, 0,6Watt
- DIN-skinne og vægmontering
- Relæudgang for advarsel om strømafbrydelse
- Driftstemperatur: -40 til +75°C
- Industri-grade design
- Mål: 135 x 87 x 32 mm





Svensk Binär Teknik

FIBER-BYPASS-LCS

SPECIFICATIONS

Data	:	Fra 100Mbps til 100Gbps, duplex eller simplex
Forsyning	:	9 - 48VDC eller 24VAC, 0,6Watt
Kabinet	:	Metal, IP30, DIN-beslag
Mål og vægt	:	135 x 87 x 32 mm, 390g



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.