

ETHIO4AI2AO7IO-P-I

High Speed 4 analogue inputs 128kHz sample rate,
24-bit, 12bit 2 analog outputs, 1 EI, 7 digital I / O, -25
- + 75 ° C, PoE

FEATURES

- 4 single ended input +/- 10V analog, +/- 5V, +/- 2.5V ... +/- 20mV
- 128kS / s for each channel sampling rate
- FIFO: 4000 samples - memory 30 million data samples
- 24bit resolution
- 2 x analog output +/- 10V, +/- 5V, 0-5 / 10V
- analog output 12bit resolution
- Trigger mode: SW, Ext analog
- 1 x 32bit counter, max. 30kHz
- 1 x Encoder input: Qadrant / CW / CCW and pulse
- 3 x digital inputs (wet) up to + 30VDC
- 4 x digital output (Open Collector) up to + 30VDC, 100mA
- Overload protection up to 1.3A
- 1 x Ethernet port RJ45
- Security: ID, password and IP filter
- Powered by the PoE or 12 - 48VDC, 2,6W
- Dimensions: 120 x 76 x 38 mm | Housing: Metal, with DIN bracket
- Operating temperature: -25 - + 75 ° C





SPECIFICATIONS

Forsyning	:	PoE eller 12 - 48VDC, 2,6Watt
Hastighed	:	128kHz sample-frekvens for alle 4 indgange
Indgang	:	4 x single-ended (fælles stel) analoge high-speed indgange
Indgang	:	3 stk. wet (forsynes med spænding) op til +30VDC
Kabinet	:	Metal, Din-beslag og vægmontering
Mål og vægt	:	120 x 76 x 38 mm, 350g
Porte	:	1 x RJ45 PoE (PD)
Trigger	:	1,5 microsekund, Falling Edge, 5VDC on, 0,8VDC off
Tæller	:	1 kanal, 32 bit, 30KHz
Udgange	:	4 stk. Open Collector, maks. +30VDC, 100mA
Udgange	:	2 x analog udgang med fælles stel, 12 bit opløsning

