

M485-MBUS-MASTER-I

M-BUS to RS232 / RS422 / RS485 MODBUS Master, 2 x
Baud rate select. M-Bus standard: A-13757, CJ /
T-188, -25 - +60°C

FEATURES

RS485 / RS422 / RS232 Master Gateway to Meter-Bus Slaves (sensors, actuators, etc.)
Supports up to 100 Meter-Bus meters (slaves)
MODBUS RTU function codes: 0x03 and 0x04 readdata
Selection of serial port, only one can be selected to be active
Baud rate x 2 (M-bus and COM port can be selected at different speeds)
Baud rate M-bUS: 300-2400 bps
Baud rate COM port: 300-115200 bps
Transparent data - no protocol conversion
M-BUS connection, 2-wire, max. 350meter.
Greater distance up to 5km requires a number M-bus repeaters
Supply voltage: 10 - 30VDC, 1.8 - 12Watt
Dimensions: 122 x 72 x 33 mm
Removable terminal blocks
Operating temperature: -25 - + 60°C
DIN mount
Robust plastic case





SPECIFICATIONS

Baudrate	:	300 - 115.200 COM-port og M-BUS 300 - 2400 (uafhængig)
Data	:	Support MODBUS RTU - code 0x03 og 0x04 (Meter data)
Forsyning	:	10 - 30VDC, 1,8 - 12Watt (afhængig af M-BUS enheder)
Interface	:	M-BUS (meter-bus) - slaver
Kabinet	:	Plast med DIN-beslag og terminal-blokke
Mål og vægt	:	122 x 72 x 33 mm
Porte	:	RS485 eller RS422 eller RS232 (MODBUS Master)

