

MODBUS / TCP to serial RTU Master Slave, Gateway, 1 x RJ45, 1 x RS232 isolated, -25 - + 75 ° C, PoE, or 12 - 48VDC

FEATURES

- Compact Modbus / TCP for RTU / ASCII Gateway with PoE
- must not be programmed
- 1 x RJ45 10 / 100Mbps
- 1 x RS232 (DB9 Han)
- Supports Modbus TCP / UDP Master and Slave
- Supports Modbus RTU / ASCII Master and Slave
- Baud Rate Up to 115,200 BPS
- Self-Tuner for RS232
- IEEE 802.3af - PoE (PD)
- Supply voltage U / Poe: 12 - 48VDC 2Watt
- Goal: 90 x 52 x 27 mm
- DIN bracket
- Operating temperature: -25 - + 75 ° C





Svensk Binär Teknik

ETH-MODGW712-I

SPECIFICATIONS

Operating Temp.	:	-25 - +75°C
Forsyning	:	PoE (PD)
Kabinet	:	Plast med DIN-beslag og terminal-blokke
Mål og vægt	:	95 x 52 x 26 mm
Porte	:	1 x RS232 (5-pin)
Porte	:	1 x RJ45 10/100Mbps



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.