

MODBUS/TCP to serial RTU Master/Slave, Gateway, 1
x 1 x RJ45 RS485 / 422 isolated, -25 - +75°C, PoE, or
12 - 48VDC

FEATURES

- Compact Modbus / TCP to RTU / ASCII gateway with PoE
- not to be programmed
- 1 x RJ45 10 / 100Mbps
- 1 x RS485 / 422 (screw terminal)
- baud rate up to 115,200 bps
- Self-tuner for RS485 / 422
- Automatic transmission / reception direction of RS485
- IEEE 802.3af - PoE (PD)
- Supply voltage u / PoE: 12 - 48VDC 2Watt
- Dimensions: 90 x 52 x 27 mm
- DIN bracket
- Operating temperature: -25 - +75°C





Svensk Binär Teknik

ETH-MODGW715-I

SPECIFICATIONS

Operating Temp.	:	-25 - +75°C
Forsyning	:	PoE (PD)
Kabinet	:	Plast med DIN-beslag og terminal-blokke
Mål og vægt	:	95 x 52 x 26 mm
Porte	:	1 x RJ45 10/100Mbps
Porte	:	1 x RS485 / RS422
Spænding	:	Uden PoE, 12 - 48VDC, 2Watt



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.