

MODBUS / TCP to serial RTU Master Slave, Gateway,
RJ45 1 x 1 x RS-232/485/422 isolated, -25 - +75°C,
PoE, or 12 - 48VDC

FEATURES

- Compact Modbus / TCP to RTU / ASCII gateway with PoE
- not to be programmed
- 1 x RJ45 10 / 100Mbps
- 1 x RS232 / RS485 / RS422 (terminal block)
- Choose only one COM port as interface
- 3-pin RS232 (RX, TX, GND)
- baud rate up to 115,200 bps
- Self-tuner for RS232
- IEEE 802.3af - PoE (PD)
- Supply voltage u / PoE: 12 - 48VDC 2Watt
- Dimensions: 90 x 52 x 27 mm
- DIN bracket
- Operating temperature: -25 - +75°C





SPECIFICATIONS

Operating Temp.	:	-25 - +75°C
Forsyning	:	PoE (PD)
Kabinet	:	Plast med DIN-beslag og terminal-blokke
Mål og vægt	:	95 x 52 x 26 mm
Porte	:	1 x RJ45 10/100Mbps
Porte	:	1 x RS232 / RS485 / RS422 (kun en kan vælges)
Spænding	:	Uden PoE, 12 - 48VDC, 2Watt

