

IPP21.5IX-1000NITS

21.5" panel PC Projected Touch i3/i5/i7 Gen.6 1000nits suitable for sunlight IP66 close front FEATURES

- 21.5 TFT LCD 1000 nits. (Available with Alm 250 CD / M2)
- Intel 6/7 Gen CPU I3 / I5 / I7. Active cooling
- H170 chipset
- max. 32GB RAM, 2x260 Pin So-Dimm DDR4 2133 MHz SDRAM
- 4 x USB-A 3.0
- 2 x RJ45 Gbit Ethernet
- 2 x RS232 / 422/485, 1 x RS232 DB9
- MPC extension
- 2x Pcie X1 / X16
- RAID Support
- IP66-rated Front
- OS Support: Win Embedded 7, 8.1 Windows 10 IoT



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

USB	:	4x USB 3.0 Type A, OPTION (4xUSB 2.0 Type A)
Operating Temp.	:	0~50°C
Approval	:	CE / FCC Class A
Ethernet	:	2 X RJ45 GbE
Forsyning	:	DC 9~36V, Option AC power input, NO 230Vac ADAPTER INCLUDED!
LCD	:	21.5 TFT LCD,
Lyd	:	Line out/Mic in
Opløsning	:	Max. Resolution1920 x 10801920 x 1080Max. Color16.7M16.7M
OS SUPPORT	:	Windows embedded 7Windows embedded 8.1Windows 10 IoT
PCI	:	1x PCIe x1 and 1x PCIe x16
Porte	:	1x DB9 RS232/422/485, 1x DB9 RS232, 1xDB9 RS422/485
SIM kort	:	OPTION: WIFI, BT, 4G antenna at rear side





Svensk Binär Teknik

IPP21.5IX-1000NITS

SPECIFICATIONS

Udgange	:	1 x VGA, 1 x HDMI
Dimensioner	:	557 x 362 x 90 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.