



Svensk Binär Teknik

UPS600

600VA/240W UPS, emergency power supply, incl. 1 piece. 12V/7Ah battery, line-interactive, 2-6 ms switch-on time

FEATURES

- Avoid data loss in the event of a power failure
- Compact Tower UPS 600VA/240Watt
- Line-interactive means switching on in case of mains failure (2-6ms)
- Emergency supply time: 50% load for approx. 6 minutes
- Noise level: Less than 40 dbA at 1 meter
- Modified sine curve (stair step curve)
- 4 hour recharge time to 90% capacity
- Auto restart when mains supply is re-established
- Battery: 1 pc. 12V/7Ah - see manual for lifespan
- Dimensions: 279 x 142 x 101 mm
- Weight with battery: 4.2 kg
- Operating temperature: 0 - + 40°C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

UPS600

SPECIFICATIONS

Operating Temp.	:	0 - +40°C
Batteri	:	12V 7Ah
Kapacitet	:	600VA/240Watt
Mål og vægt	:	279 x 142 x 101 mm, 4,2 kg med batteri
Udgangsspænding	:	230VAC 50Hz modificeret sinusurve



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.