



Svensk Binär Teknik

UPS800

800VA/480W UPS uninterruptible power supply, incl.
1 pc. 12V/9Ah battery, line-interactive, on time 2-6
ms, Simulated sine curve

FEATURES

- To prevent loss of data during power failure
- Compact Tower UPS 800VA / 480Watt
- Line-interactive means switching at power failure (2-6ms)
- Nødforsynings time: 50% load for about 3 minutes
- Noise level: Less than 40 dbA at 1 meter
- Modified sine wave (staircase curve)
- 4-6 hour recharge time to 90% capacity
- Auto restart on mains supply restored
- Supports automatic shutdown via software
- Battery: 1 pc. 12V / 7Ah - see manual for life
- Dimensions: 279 x 142 x 101 mm
- Weight with battery: 4.9 kg
- Operating temperature: 0 - + 40 ° C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

UPS800

SPECIFICATIONS

Operating Temp.	:	0 - +40°C
Batteri	:	12V 9Ah
Kapacitet	:	480Watt / 800VA
Mål og vægt	:	279 x 142 x 101 mm, 4,9 kg med batteri
Udgangsspænding	:	230VAC 50Hz modificeret sinuskurve



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.