



Svensk Binär Teknik

UPS1500

1500VA/900W UPS power supply, incl. 2 pcs. 12V / 9aH battery, line-interactive, on time 2-6 ms, Simulated sine curve

FEATURES

- To prevent loss of data during power failure
- Compact Tower UPS 1500VA / 900Watt
- Output voltage: 230VAC / 50Hz
- Line-interactive means switching at power failure (2-6ms)
- Backup time: 50% load for about 6 minutes
- Noise level: Less than 40 dbA at 1 meter
- Modified sine wave (staircase curve)
- 4-6 hour recharge time to 90% capacity
- Auto restart on mains supply restored
- Supports automatic shutdown via software
- Battery: 2 pcs. 12V / 9Ah - see manual for life time
- Dimensions: 320 x 182 x 130 mm
- Weight with battery: 10.6 kg
- Operating temperature: 0 - + 40 ° C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

UPS1500

SPECIFICATIONS

Operating Temp.	:	0 - +40°C
Batteri	:	2 x 12V/9Ah
Kapacitet	:	900Watt / 1500VA
Mål og vægt	:	320 x 182 x 130 mm, 10,6 kg med batteri
Udgangsspænding	:	230VAC / 50Hz modificeret sinuskurve (trappetrin)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.