

1000VA/600W UPS power supply, incl. 2 pcs. 12V/7Ah battery, line-interactive, on time 2-6 ms, Simulated sine curve

FEATURES

- To prevent loss of data during power failure
- Compact Tower UPS 1000VA / 600Watt
- Output voltage: 230VAC / 50Hz
- Line-interactive means switching at power failure (2-6ms)
- Battery time: 25% load for about 18 minutes
- Noise level: Less than 40 dbA at 1 meter
- Modified sine wave (staircase curve)
- 4-6 hour recharge time to 90% capacity
- Auto restart on mains supply restored
- Supports automatic shutdown via software
- download USB and RJ45 port, touch display
- Battery: 2 pcs. 12V / 7Ah - see manual for life
- Not suitable for printers and scanners
- Dimensions: 320 x 182 x 130 mm
- Weight with battery: 8.2 kg
- Operating temperature: 0 - + 40 ° C





Svensk Binär Teknik

UPS1000I

SPECIFICATIONS

Operating Temp.	:	0 - +40°C
Batteri	:	2 stk. 12V/7Ah
Kapacitet	:	600Watt / 1000VA
Mål og vægt	:	320 x 182 x 130 mm, 8,2 kg med batteri
Udgangsspænding	:	230VAC / 50Hz modificeret sinuskurve



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.