

10.1" Fanless Panel PC IP66 / 69K near the front and back. Multi-touch

FEATURES

- 10.1 " TFT LED panel with Capacitive touch display
- Intel® Pentium® N4200
- System memory max 8G SDRAM
- Internal SATA 2.5" HDD and m.2 2242 socket
- M12 Connectors 1 GbE LAN, 1 2xUSB2.0, 1COM
- VESA and Yoke mounting
- 9~36 V DC Power Input Connectors (Waterproof switch)
- 20~60° C Operating Temperature





SPECIFICATIONS

CPU	:	Intel Pentium N4200 1.1GHz/2.5GHz (boost)
USB	:	2xUSB 2.0 (m12 connector)
Operating Temp.	:	-20 ~60° C (-4~ 158° F) w/ 2.5" HDD (Operational humidity: 60° C @ 95% RH Non-Condensing)
BIOS	:	UEFI
Chok/Vibration	:	1 Grms, IEC 60068-2-64, random, 5~500 Hz, 1 Oct/min., 1hr/axis, x, y, z 3 axes Shock: 20 G, IEC 60068-2-27, half sine, 11 ms duration
Ethernet	:	1x Gbe 10/100/1000 Mbps (intel i211AT) (M12 connector)
Forsyning	:	9~36Vdc input M12 connector typical 12W max 21.6W
Hukommelse	:	2 x DDR3L 1866MHz SD MAX.8GB
Lysstyrke	:	500cd/m2
Montering	:	75x75mm, 100x100mm, eller Option Yoke Mount
Msata	:	1 M.2 B/N key 2242
OS SUPPORT	:	windows 10 IOT, Linux





Svensk Binär Teknik

IPP10.1IP66F

SPECIFICATIONS

Skærm	:	10.1" 1280x800
Synsfelt	:	75 x 80 (H) x 80 x 80 (V)
Touch	:	Projected capacitive 90% transparency 7 Mohs hardness
Udgange	:	Option! : 1 x VGA up to 1920x1200 60Hz M12 connector
Weight	:	3.145Kg
Dimensioner	:	310 x 79.5 x 210 mm (12.2"x 3.13"x 8.26")



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.