

10.1" Panel PC full IP66/IP69K celeron 2930 4GB RAM, 32GB MLC SSD

FEATURES

- 10.1" Stainless Steel Panel PC
- 350 cd/m²
- Intel Celeron N2930 1.83 GHz Onboard Processor
- 8GB Onboard DDR3L SDRAM max. 8GB total
- Flat front frame Design
- grade 304 stainless steel housing (Grade 316 is Option)
- IP66 / IP69K Rated with M12 connector
- Support resistive touch, expected capacitive touch, and Glass Touch
- on / off button on the side Edge for hygienic cleaning
- Support Ergonomic Versatile Mounting: Yoke Mounting / Space-saving VESA 75 x 75 mm Mounting
- OPTION HIGH BRIGHTNESS 1000cd/m²





IPP10.1IP65F2

SPECIFICATIONS

CPU	:	Celeron N2930 2M cache, 1.83GHz
USB	:	1 x M12 8 pin USB 2.0 waterproff cover and chain
Operating Temp.	:	0~50oC
Antal farver	:	16.7M
Approval	:	CE/FCC class A
Ethernet	:	1 x M12 8 pin for LAN with waterproff cover and chain
Forsyning	:	9~36Vdc , power consupion 18Watt
Hukommelse	:	Onboards 4GB DDR3L SDRAM, Max 8GB(option)
LCD	:	10.1"TFT 1280x800
Montering	:	VESA mount 75x75, Option Yoke Mount
OS SUPPORT	:	Windows embedded 7, 8.1 and windows 10 IoT ENT LTSB
Porte	:	1 x M12 8 pin COM1, RS232/422/485 default RS232 with waterproff cover and Chain





Svensk Binär Teknik

IPP10.1IP65F2

SPECIFICATIONS

Synsfelt	:	170(H)x170(V)
Touch	:	Resistive Touch USB, light transmission 80%. Option GLASS and Projected touch
Dimensioner	:	300x220x53mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.