

Ethernet over PDS cable, RJ45 UTP cable, 500m with data and PoE over the cable. VDSL. Set of 2 units.  
PoE up to 38Watt

## FEATURES

Network Extender of RJ45 UTP patch cable  
PoE transmitted in the cable from the PSE to the PD  
1 x 10 / 100Mbit BASE-TX RJ45  
Data rate: 94 - 30Mbps auto-optimization  
Auto -negotiation / auto-MDI / MDI-X  
PoE Standard: IEEE 802.3at / PoE of  
Output: 48-56VDC max. 38 Watt  
1 x RJ45 to VDSL + PoE  
PoE pin: Pin 1/3/5/7 (+ ) 2/4/6/8 (-)  
Distance: 100m m / PoE +, 500m w / PoE, without  
PoE 1000m  
Powered by the 48-56VDC min. 2Amp





Svensk Binär Teknik

ETH-VDSL-UTP+P

## SPECIFICATIONS

|                 |   |                                     |
|-----------------|---|-------------------------------------|
| Operating Temp. | : | -20 - +70°C                         |
| Forsyning       | : | PSE Injektoren: 44 - 56VDC maks. 2A |
| PoE             | : | Maks. 25 - 38 Watt                  |
| Standarder      | : | IEEE 802.3af/at PoE PSE og PD       |
| Dimensioner     | : | 94 x 70 x 26 mm                     |



Binär Teknik AB  
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.