

4 Port Industrial Router with PoE +, Management,
10/100 / 1000Mbit 4 x RJ45 LAN, 1 x RJ45 WAN / LAN,
1 x USB 3.0, -10 - + 60 ° C

FEATURES

- 4-port 10/100 / 1000BASE-T RJ45 with IEEE 802.3af / 802.3at PoE injector
- 1-port 10/100 / 1000BASE-T RJ45 WAN port or LAN port interface (router mode or switch mode)
- 1 x USB 3.0 port for backing up and restoring configuration file
- PoE power is 36Watt per port - automatically Detect PD
- PoE monitoring, status, strömbudg PoE port enable / disable, PD live check
- IP30 metal housing, DIN bracket
- Dimensions: 180 x 140 x 25 mm | Operating temperature: -10 - + 60 ° C
- Supply voltage: 48V ~ 56V DC (PSU purchased)
- Supports IEEE 802.1Q / D
- Security: port filter, MAC filter, IP source protection, anti-DoS





Svensk Binär Teknik

ETH-ROUTER-4POE+U

SPECIFICATIONS

Forsyning	:	48 - 56VDC, maks. 134Watt
Kabinet	:	Metal, IP30, magneter på bagplade, flange-montering
Mål og vægt	:	180 x 140 x 25mm, 728g
PoE	:	36Watt per port. Power budget er 120Watt



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.