

ETHIO8I8O-P2I+

8 x DI Wet/Dry 0 - +50VDC 500Hz, 8 x DO +40VDC
650mA, 2 x RJ45, Modbus TCP/UDP, PoE and 12 -
48VDC

FEATURES

- Built-in Web server
- Web HMI
- Modbus TCP and Modbus UDP protocols
- Good communication security
- Dual Watchdog
- Operating temperature range: -25 ~ + 75 ° C
- I/O Pair - Input Mirrors at the second's output
- 8 x Digital input (counter): 0 - + 50VDC (500Hz) -
Wet / Dry
- 8 x Digital output: Open Collector 0 - + 40VDC /
650MA per Ch
- 2 x RJ45 Ethernet - Daisy Chain
- Supply voltage: POE or 12 - 48VDC / 4Watt





ETHIO8I8O-P2I+

SPECIFICATIONS

Forsyning	:	PoE eller 12 - 48VDC, 4Watt
Indgang	:	8 stk. Wet (tilfør volt) eller Dry (kontakt)
Netværk	:	10/100Mbit 2 x RJ45 PoE og data til Daisy chain
Protokol	:	Modbus/TCP / UDP
Tæller	:	Indgange som 32 bit tæller 500Hz
Udgange	:	8 stk. Open Collector maks. 40VDC 650mA/ch

