

DC24V2.5A-D

24VDC 60W Power supply from 85VAC-264VAC. 24V / 2.5A, adjustment 21.6-29V, DIN mounting

FEATURES

- AC / DC power supply for your rail mounting
- AC Input: 85 - 264Vac
- Effect: 60W
- Output voltage: 24V / 2.5A
- Screw terminal
- Adjustable output voltage for 24 to 29V
- Working temperature: -30 - + 70 ° C
- Dimensions: 90 x 54.5 x 62.5 mm (H, D, B)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



Svensk Binär Teknik

DC24V2.5A-D

SPECIFICATIONS

Operating Temp.	:	-30°C to +70°C
Indgang	:	120 til 370 VDC, 85 til 264 VAC
Montering	:	DIN skin
Standarder	:	RoHS, TUV EN 60950-1, UL 508
Type	:	Switch-mode
Udgange	:	24VDC 2.5A 60W
Dimensioner	:	90 x 54.5 x 52.5 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.