

2 Mega Pixel bullet IP camera, Anti corrosion, Steel housing, IP68 / IP69, -40°C - +65°C

FEATURES

- 316L Stainless Steel Housing
- Anti-corrosion
- NEMA-4X, IP68/ IP69
- 2 Megapixel IR Bullet IP Camera
- H.264+/ H.264/ M-JPEG Compression
- Smart Focus System for Remote Focus Adjustment
- Digital Noise Reduction
- Power over Ethernet
- Day Night Manual Switch Time Control
- Operating Temperature -40°C~65°C with Heater
- IR LED Built-in 45M/span
- IR Cut Filter Mechanism
- Micro SD Card Backup
- 2-way Audio
- Support iPhone/Android/Mac
- SDK for Software Integration
- Free Bundle 36 Ch Recording Software





SPECIFICATIONS

Operating Temp.	:	-40°C~70°C
I/O	:	D1x1, D0x1, RJ45, DC JACK, BNC Output, Micro SD card slot built-in (optional)
IP-Tæthed	:	IP68, IP69
Linse	:	2.8-12mm 4.2X Bulid-in Zoom Lens @ F1.4
Lyd	:	Audio Format G.711 (64K) / G.726 (32K, 24K) Audio Input: External line in Output: External line out Support 2 way audio
Lysfølsomhed	:	Color 0.005 lux, (AGC ON)
Opløsning	:	1920x1080@30fps 1280x720@30fps 640x360@30fps (2M)
PoE	:	Max:8.16W(IR ON), 3.36W(IR OFF)
Protokol	:	IPv6, IPv4, HTTP, HTTPS, SNMP, SSL, TLS, DNS, ICMP, IGMP, ARP, SNTP, QoS/DSCP, IEEE 802.1X, RTSP/RTP/RTCP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, SAMBA, Bonjour, Google Drive, Dropbox, ONVIF Profiles
Sensor	:	1/2.8" Sony True WDR Starvis CMOS Sensor
Strømforbrug	:	DC 12 Max:7.53W(IR ON), 2.28W(IR OFF)
Weight	:	2,25Kg





Svensk Binär Teknik

KAM-2M-STEEL

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.