

KAM-U-BULL5MP-LED

Outdoor 5MP white LED bullet camera with Wide Dynamic Range. PoE or 12vdc.

FEATURES

- 1/3" Progressive Scan CMOS
- 5MP 2560 (H) × 1920 (V)
- Hvid LED rækkevidde Op til 20 m
- IR rækkevidde Op til 20 m
- IP66
- Driftstemperatur : -35 ° C ~ 55 ° C
- Indbygget micro SD slot, op til 256 GB
- Vægt: 350g



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

Operating Temp.	:	-35°C ~ 55°C (-31°F ~ 131°F)
Andet	:	Streaming Capability: 2 Streams
Forsyning	:	DC12V/POE (IEEE 802.3af) Max 8W
Features	:	ONVIF, SDK
IP-Tæthed	:	IP66
Lysstyrke	:	White LED range up to 20 m, IR range up to 20 m
Maks. opløsning	:	2560(H)×1920(V)
Protokol	:	IPv4, RTSP/RTP/RTCP, TCP/UDP, HTTPS, DHCP, DNS, DDNS, UPNP, ICMP, IGMP, NTP, SMTP, 802.1x, SNMP
Sensor	:	1/3" Progressive Scan CMOS

