


Fanless ATOM PC 2xSIM, DVI, HDMI, 3xEthernet,
4xCOM, -20°C~70°C, DIN or wall mount IOT Gateway
delivered up to 15 years

FEATURES

- Intel® Atom® x6414RE/x6212RE Processors (formerly Elkhart Lake)
- GPIO 4-in/4-out & 1x DVI-I & 1x HDMI
- 1x M.2 B-Key 3052 support 5G module
- Optional 1x 2.5" SSD (needs to be ordered)
- 3x 2.5G Ethernet port
- 3x full-size Mini PCI-E sockets
- 4x COM (RS232/422/485)
- 2x USB 3.1 & 2x USB 2.0
- Supports DIN-rail mount, wall mount
- TPM 2.0
- Extended operating temperature from -20°C to 70°C
- 9V~36V DC wide-range power input
- Over/Under/Reverse voltage protection





SPECIFICATIONS

CPU	:	Intel® Atom® x6414RE (1.5GHz, 1.5MB cache, 9W TDP) or as option Intel® Atom® x6212RE (1.2GHz, 1.5MB cache, 6W TDP)
USB	:	2x USB 3.1 ports, 2x USB 2.0 port
Operating Temp.	:	-20°C~70°C (-4°F~158°F)
Andet	:	2 x antenna hole for wlan module (NOT INCLUDED)
Approval	:	CE/ FCC/ LVD
Chok/Vibration	:	Vibration Operating: 2.0 Grms / 5~500Hz / random operation (with IEC 60068-2-64) Shock Operating: 30G/11 ms Duration Non-operating: 40G/11 ms Duration
Ethernet	:	3 x RJ45 2.5G Ethernet port
Forsyning	:	9V-36Vdc, 1x 3-pin DC-in terminal block, 1x power button with Green LED
GPIO	:	1x 4-in & 4-out GPIO
Hukommelse	:	1 x 4GB DDR4-3200 SO-DIMM, Max. 16GB
Luftfugtighed	:	5~90% @ 60°C, (non-condensing)
Lyd	:	1x Line-out/ Mic-in





Svensk Binär Teknik

EPC-ATOM-3E4C4IODIN

SPECIFICATIONS

Montering	:	DIN-rail mounting (DIN-rail mount kit included) Desktop or wall mounting (wall mount kit included)
OS SUPPORT	:	Win10 and Linux Ubuntu
Porte	:	4x RS232/422/485
Udgange	:	1x DVI-I, 1x HDMI
Dimensioner	:	218mm(W) x 110mm(D) x 57mm(H) w/ Wall mount kit 8.58"(W) x 4.33"(D) x 2.24"(H)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.